



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

1. Product And Company Identification

Product Name: STP® High Mileage Power Steering Fluid + Stop Leak

Responsible Party: STP Products Manufacturing Company
44 Old Ridgebury Road
Suite 300
Danbury, CT 06810

Information Phone Number: +1 203-205-2900

Emergency Phone Number:

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for
Outside US and Canada (call collect)

SDS Date of Preparation: 01/30/2018

Product Use: Automotive maintenance product – For consumer and professional use

2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

GHS Classification:

Physical:	Health:
Not Hazardous	Toxic to Reproduction Category 1B

GHS Label Elements:



Danger!

Statements of Hazard	Precautionary Phrases
May damage fertility by ingestion.	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective clothing. IF exposed or concerned: Get medical attention. Store locked up. Dispose of contents and container in accordance with local and national regulations



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

3. Composition/Information on Ingredients

Component	CAS No.	Amount
Mineral Oil	64742-54-7 / 64742-65-0	80 - 100%
Benzyl butyl phthalate	85-68-7	0 - 3%

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Get medical attention if symptoms appear and persist.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash exposed skin with soap and water. If skin irritation or redness develops, get medical attention. High pressure injection of this product through the skin is a medical emergency. This product must be removed completely from under the skin. Seek immediate medical attention.

Eye Contact: Flush eyes with plenty of water. If irritation or other symptoms persist, seek medical attention.

Ingestion: Do not induce vomiting unless directed to by doctor or physician. If the victim is fully conscious, have them drink a glass of water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

Most Important Symptoms: Direct eye contact may cause mild irritation. Inhalation of mists or vapors generated at elevated temperatures may cause respiratory irritation. Prolonged skin contact may cause dryness and defatting. High pressure injection of this product through the skin is a medical emergency. May damage fertility by ingestion.

Indication of Immediate Medical Attention/Special Treatment: High pressure injection of this product through the skin is a medical emergency.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Will burn under fire conditions. Closed containers may rupture if exposed to extreme heat. Burning may produce carbon monoxide and carbon dioxide, zinc oxide and hydrocarbons.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Caution – slip hazard. Eliminate all ignition sources and ventilate the area. Wear appropriate protective equipment.

Environmental Precautions: Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations. Notify the National Response Center if a spill of any amount enters navigable waters, the contiguous zone, or adjoining shorelines.

Methods for Containment and Clean-Up: Stop spill at the source if it is safe to do so. Absorb with an inert material. Collect into a suitable container for disposal. Clean area as appropriate since spilled materials, even in



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

small quantities, may present a slip hazard.

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors and mists. Wash exposed skin thoroughly with soap and water after use. Keep containers closed when not in use. Keep out of the reach of children.

Empty containers retain product residue and may be hazardous. Do not reuse empty containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area. Store away from oxidizing agents and other incompatible materials.

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
Petroleum lubricating oil (Oil mist)	5 mg/m ³ inhalable TWA ACGIH TLV 5 mg/m ³ TWA OSHA PEL (as mist)
Benzyl butyl phthalate	None Established

Engineering Controls: General ventilation should be adequate for all normal use. For operations where the TLV may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions. For operations where the TLV is exceeded, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Gloves: None normally required. Impervious gloves such as neoprene or nitrile are recommended if needed to avoid prolonged or repeated skin contact.

Eye Protection: None required for normal use. Avoid eye contact. Safety glasses or goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required under normal use conditions.

9. Physical and Chemical Properties

Appearance And Odor: Light red liquid with a lubricating oil odor.

Physical State: Liquid	Odor Threshold: Not determined
pH: Not applicable	Specific Gravity: 0.88
Initial Boiling Point/Range: >620°F (>327°C)	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: Not determined



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

Solubility In Water: Negligible	Percent Volatile: Nil
Viscosity: 41.4 – 50.6 cSt @ 40°C	Evaporation Rate: Very slow
Coefficient Of Water/Oil Distribution: Not determined	VOC Content: Not determined
Flash Point: >300°F (>149°C) COC minimum	Autoignition Temp: Not determined
Decomposition Temperature: Not determined	Flammability Limits: LEL: Not determined UEL: Not determined
Flammability (solid, gas): Not applicable	

10. Stability and Reactivity

Reactivity: Not normally reactive

Chemical Stability: Stable.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Keep away from excessive heat and open flames.

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: May produce carbon monoxide, carbon dioxide, zinc oxide and hydrocarbons.

11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

Acute Hazards:

Inhalation: Inhalation of mists or vapors generated at elevated temperatures may cause upper respiratory tract irritation.

Skin Contact: Prolonged or repeated skin contact may cause irritation and dryness. High pressure injection of this product through the skin may cause possible extensive tissue damage resulting in loss of a finger, hand or arm. There may be no sign of initial injury or pain.

Eye Contact: Direct contact may cause slight eye irritation.

Ingestion: Swallowing may cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Chronic Hazards: May damage fertility by ingestion.

Carcinogenicity Listing: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

Acute Toxicity Values:

Petroleum lubricating oil (as Mineral Oil):

LD50 Oral Rat: >5,000 mg/kg

LD50 Skin Rabbit: >5,000 mg/kg

Benzyl butyl phthalate:

LD50 Oral Rat: 2,330 mg/kg

12. Ecological Information

Ecotoxicity:



Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

Petroleum lubricating oil (as Mineral Oil):

LC50 Rainbow trout (*Oncorhynchus mykiss*): > 5,000 mg/L/ 96hr.

LC50 water flea (*Daphnia magna*): > 1,000 mg/L / 48hr.

Benzyl butyl phthalate:

LC50 *Oncorhynchus mykiss* 0.82 mg/L/ 96 hr

Persistence and Degradability:

No data available.

Bio accumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects: No data available.

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: Not Regulated

Canadian TDG Hazardous Materials Description: Not Regulated

IMDG Dangerous Goods Description: Not Regulated

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has an RQ of 3300 lbs based on the RQ for Benzyl butyl phthalate of 100 lbs. present at 3% maximum. Oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Chronic Health

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): Zinc compounds below de minimus concentration.

Canada:

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian DSL.

16. Other Information



® Safety Data Sheet

STP Products Manufacturing Company

44 Old Ridgebury Road
Suite 300
Danbury, CT 06810
Tel. 1-203-205-2900

NFPA Rating (NFPA 704): Health: 1 Fire: 1 Instability: 0
HMIS Rating: Health: 1* Fire: 1 Physical Hazard: 0
*Chronic Health Hazard

REVISION DATE: 01/30/2018

REVISION SUMMARY: New SDS. Formula template.

DATE OF PREVIOUS REVISION: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH